



Fire ratings are available in most JELD-WEN® Door product lines. There may be restrictions based on size and regional availability, so please use this sheet as a reference and discuss further with your JELD-WEN supplier. All door slabs must be used with fire-rated door systems for true fire protection. A door system consists of the door slab, frame, hardware and components.

Exterior Doors					
Product Type	Ratings	Models	Largest Slab Size		
IWP® Wood Doors	20-Minutes	<ul style="list-style-type: none"> • Fire-rated solid core • 1-3/4" to 2-1/4" doors 	Available with all-panel doors Radius top doors up to 60-Minutes Segment top doors up to 90-Minutes Select 20- and 45-Minute doors available with glass (Custom quoted)	4'0" x 8'0" Single* 7'0" x 8'0" Pair*	
	45-Minutes	<ul style="list-style-type: none"> • FyreWerks® core • 1-3/4" to 2-1/4" doors 			
	60-Minutes	<ul style="list-style-type: none"> • FyreWerks core • 1-3/4" to 2-1/4" doors 			
	90-Minutes	<ul style="list-style-type: none"> • FyreWerks core • 1-3/4" to 2-1/4" doors 			
Fiberglass Doors	20-Minutes	<ul style="list-style-type: none"> • Fire-rated solid core • 1-3/4" doors • Laminated Veneer Lumber (LVL) or wood stiles and rails • LFI-capped top rail and PVC-capped stiles and bottom rails 	Available with all-panel doors Design-Pro™ Fiberglass Doors Smooth-Pro™ Fiberglass Doors	3'0" x 8'0" Single 6'0" x 6'8" Pair	
Steel Doors	20-Minutes	<ul style="list-style-type: none"> • Wood edge 	Available with Contours™ all-panel doors	3'0" x 6'8" Single 3'0" x 8'0" Single 6'0" x 7'0" Pair 3'6" x 7'0" Single	
	20-, 45-, 60- and 90-Minutes	<ul style="list-style-type: none"> • Steel edge 			
Aurora® Fiberglass Doors	20-Minutes		Available in all-panel designs. Arch tops approved.	3'0" x 8'0" Single	
Interior Doors					
Product Type	Ratings	Models	Largest Slab Size		
IWP® Wood Doors	20-Minutes	<ul style="list-style-type: none"> • Fire-rated solid core • 1-3/4" to 2-1/4" doors 	Available with all-panel doors Radius top doors up to 60-Minutes Segment top doors up to 90-Minutes Select 20- and 45-Minute doors available with glass (Custom quoted)	4'0" x 8'0" Single* 7'0" x 8'0" Pair*	
	45-Minutes	<ul style="list-style-type: none"> • FyreWerks core • 1-3/4" to 2-1/4" doors 			
	60-Minutes	<ul style="list-style-type: none"> • FyreWerks core • 1-3/4" to 2-1/4" doors 			
	90-Minutes	<ul style="list-style-type: none"> • FyreWerks core • 1-3/4" to 2-1/4" doors 			
Premium Composite Doors	20-Minutes	<ul style="list-style-type: none"> • Fire-rated solid core • 1-3/4" doors 	Available with all raised panel doors Available in recessed panel doors with largest slab size of 3'0" x 6'8"	3'0" x 8'0" Single 6'0" x 8'0" Pair	
Molded Doors	20-Minutes	<ul style="list-style-type: none"> • Wood-based panel core • 1-3/4" doors 	Available in all standard models except Impression™ Series doors	3'0" x 8'0" Single 6'0" x 8'0" Pair	
	45-Minutes	<ul style="list-style-type: none"> • Solid Mineral core • 1-3/4" doors 	Craftsman III™ and Conmore® Smooth doors available with 20-Minute Fire rating for 3'0" x 7'0" maximum size	3'6" x 7'0" Single 3'0" x 8'0" Single 6'0" x 8'0" Pair	
	60-Minutes	<ul style="list-style-type: none"> • Solid Mineral core • 1-3/4" doors 	Madison™ and Monroe® Smooth doors available with 20-Minute Fire rating for 3'0" x 8'0" maximum size		
Flush Doors	20-Minutes	<ul style="list-style-type: none"> • Wood-based panel core • 1-3/4" doors 	Available in all models	4'0" x 8'0" Single 8'0" x 8'0" Pair	
	45-Minutes	<ul style="list-style-type: none"> • Solid Mineral core • 1-3/4" doors 			Glass available up to 1,296 square inches, depending on fire rating
	60-Minutes	<ul style="list-style-type: none"> • Solid Mineral core • 1-3/4" doors 			
	90-Minutes	<ul style="list-style-type: none"> • Solid Mineral core • 1-3/4" doors 			

*Size limitations for IWP Wood fire-rated doors in fire-rated wood jamb: 20-Minutes: 3'6" x 8'0" single, 5'6" x 8'0" pair; 45/60/90-Minutes: 3'6" x 8'0" single